

Close control with remote condenser

CD 031-071



10-22.1 kW



407C



Scroll

Technical features

- UNDER version air down flow
- OVER version air up flow
- Centrifugal fan double inlet directly coupled
- Scroll compressors
- Advanced microprocessor control interface user and semi-graphic LCD display
- EU4 filters
- Frontal access for maintenance

Accessories and options

- Adjustable base frame
- Air delivery plenum
- Double pannels (sandwich)
- Electric post-heating coil
- EU5 or EU7 filters
- Humidification/dehumidification option
- LAN connection or remote monitoring systems
- Rear return air (only for up flow version)



Technical feature

CD 031-071		031	041	051	061	071
Total cooling capacity	kW	10	12,8	15,3	20,5	22,1
Sensible cooling capacity	kW	9,3	12	13,9	19,3	20,5
Nominal air flow	m ³ /s	0,75	1,11	1,11	1,67	1,67
Sound pressure level* (up/down flow)	dB(A)	52/48	55/51	55/51	55/51	56/52
Dimensions						
Lenght	mm	650	840	840	1.238	1.238
Width	mm	650	650	650	650	650
Height	mm	1.970	1.970	1.970	1.970	1.970

* Sound pressure level measured at 2 m from the machine and at 1 m from the ground in free field conditions.